



2. **Soft Gloss Fortified Acrylic House Paint, Benjamin More MoorGlow 096 or equal.** 100% Acrylic Latex House Paint, semi-gloss paint fortified with alkyd resin. Soap and water clean up. Resistant to fading, cracking, peeling, blistering, dirt pick-up, alkali and fumes. Mildew resistant.

<b>Product Information</b>																																																									
<p><b>Colors: —Standard:</b> Country Redwood 23, Heritage Red 25, Classic Burgundy 26, Hamilton Blue 36, Chrome Green 41, Essex Green 43, Black Forest Green 46, Charleston Brown 66, Black 80, Charcoal Slate 86</p> <p><b>—Low Temperature:</b> Brilliant White 01, Cottage Red 22, Richmond Blaque 54, Tudor Brown 62, Annapolis Gray 70, Platinum Gray 71, Navajo White 72, Briarwood 73, Cliffside Gray 74, Montgomery White 76, Sailcloth 77, Lancaster White 78</p> <p><b>—Tint Bases:</b> Benjamin Moore® Color Preview® bases 3B &amp; 4B</p> <p><b>—Low Temperature Tint Bases:</b> Benjamin Moore® Color Preview® bases 1B &amp; 2B</p> <p><b>—Special Colors:</b> Contact your Benjamin Moore &amp; Co. representative</p> <p><b>Certification:</b> Formulated without lead or mercury. Very low in VOCs.</p> <p><b>Federal Specifications Generic Equivalent</b> Exterior: TT-P-19-D</p> <p><b>Technical Assistance</b> Available through your local authorized independent Benjamin Moore &amp; Co. dealer. For the location of the dealer nearest you, call 1-800-826-2623, see <a href="http://www.benjaminmoore.com">www.benjaminmoore.com</a>, or consult your local Yellow Pages.</p>	<table border="1"> <thead> <tr> <th style="text-align: left;"><b>Technical Data</b></th> <th style="text-align: left;"><b>Brilliant White</b></th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td>100% Acrylic Latex</td> </tr> <tr> <td>Pigment Type<sup>o</sup></td> <td>Titanium Dioxide</td> </tr> <tr> <td>Volume Solids<sup>o</sup></td> <td>41%</td> </tr> <tr> <td>Theoretical Coverage At Recommended Film Thickness</td> <td>400 – 450 Sq. Ft.</td> </tr> <tr> <td>Recommended Film Thickness – Wet</td> <td>3.8 mils</td> </tr> <tr> <td style="text-align: right;">– Dry</td> <td>1.5 mils</td> </tr> <tr> <td>Dry Time @ 77° F — Set To Touch</td> <td>3 Hours</td> </tr> <tr> <td>(25° C) @ 50% RH — To Handle</td> <td>4 Hours</td> </tr> <tr> <td style="text-align: right;">– To Recoat</td> <td>4 Hours</td> </tr> <tr> <td style="text-align: right;">– To Hard Dry</td> <td>Overnight</td> </tr> <tr> <td colspan="2"><i>High humidity or cooler temperatures may prolong drying time.</i></td> </tr> <tr> <td>Dries By</td> <td>Evaporation, Coalescence</td> </tr> <tr> <td>Viscosity<sup>o</sup></td> <td>95 ± 2 KU</td> </tr> <tr> <td>Flash Point (Seta)</td> <td>None</td> </tr> <tr> <td>60° Specular Gloss</td> <td>Semi-Gloss</td> </tr> <tr> <td>Surface Temperature at application</td> <td> <table border="0"> <tr> <td style="padding-right: 10px;"><i>Standard colors and bases</i></td> <td rowspan="2" style="font-size: 2em; vertical-align: middle;">}</td> <td>– Min. 50° F</td> </tr> <tr> <td></td> <td>– Max. 90° F</td> </tr> <tr> <td></td> <td rowspan="2" style="font-size: 2em; vertical-align: middle;">}</td> <td>– Min. 35° F</td> </tr> <tr> <td style="padding-right: 10px;"><i>Low-temp colors</i></td> <td>– Max. 90° F</td> </tr> </table> </td> </tr> <tr> <td>Thin With</td> <td>Clean Water</td> </tr> <tr> <td>Clean Up Thinner</td> <td>Clean Water</td> </tr> <tr> <td>Weight Per Gallon<sup>o</sup></td> <td>11.0 lbs.</td> </tr> <tr> <td>Storage Temperature – Min.</td> <td>40° F</td> </tr> <tr> <td style="text-align: right;">– Max.</td> <td>90° F</td> </tr> <tr> <td colspan="2"> <b>Volatile Organic Compounds (VOC)</b>  <i>Unthinned, this product is formulated not to exceed 250 Grams/Liter. **</i> </td> </tr> </tbody> </table>	<b>Technical Data</b>	<b>Brilliant White</b>	Vehicle Type	100% Acrylic Latex	Pigment Type <sup>o</sup>	Titanium Dioxide	Volume Solids <sup>o</sup>	41%	Theoretical Coverage At Recommended Film Thickness	400 – 450 Sq. Ft.	Recommended Film Thickness – Wet	3.8 mils	– Dry	1.5 mils	Dry Time @ 77° F — Set To Touch	3 Hours	(25° C) @ 50% RH — To Handle	4 Hours	– To Recoat	4 Hours	– To Hard Dry	Overnight	<i>High humidity or cooler temperatures may prolong drying time.</i>		Dries By	Evaporation, Coalescence	Viscosity <sup>o</sup>	95 ± 2 KU	Flash Point (Seta)	None	60° Specular Gloss	Semi-Gloss	Surface Temperature at application	<table border="0"> <tr> <td style="padding-right: 10px;"><i>Standard colors and bases</i></td> <td rowspan="2" style="font-size: 2em; vertical-align: middle;">}</td> <td>– Min. 50° F</td> </tr> <tr> <td></td> <td>– Max. 90° F</td> </tr> <tr> <td></td> <td rowspan="2" style="font-size: 2em; vertical-align: middle;">}</td> <td>– Min. 35° F</td> </tr> <tr> <td style="padding-right: 10px;"><i>Low-temp colors</i></td> <td>– Max. 90° F</td> </tr> </table>	<i>Standard colors and bases</i>	}	– Min. 50° F		– Max. 90° F		}	– Min. 35° F	<i>Low-temp colors</i>	– Max. 90° F	Thin With	Clean Water	Clean Up Thinner	Clean Water	Weight Per Gallon <sup>o</sup>	11.0 lbs.	Storage Temperature – Min.	40° F	– Max.	90° F	<b>Volatile Organic Compounds (VOC)</b> <i>Unthinned, this product is formulated not to exceed 250 Grams/Liter. **</i>	
<b>Technical Data</b>	<b>Brilliant White</b>																																																								
Vehicle Type	100% Acrylic Latex																																																								
Pigment Type <sup>o</sup>	Titanium Dioxide																																																								
Volume Solids <sup>o</sup>	41%																																																								
Theoretical Coverage At Recommended Film Thickness	400 – 450 Sq. Ft.																																																								
Recommended Film Thickness – Wet	3.8 mils																																																								
– Dry	1.5 mils																																																								
Dry Time @ 77° F — Set To Touch	3 Hours																																																								
(25° C) @ 50% RH — To Handle	4 Hours																																																								
– To Recoat	4 Hours																																																								
– To Hard Dry	Overnight																																																								
<i>High humidity or cooler temperatures may prolong drying time.</i>																																																									
Dries By	Evaporation, Coalescence																																																								
Viscosity <sup>o</sup>	95 ± 2 KU																																																								
Flash Point (Seta)	None																																																								
60° Specular Gloss	Semi-Gloss																																																								
Surface Temperature at application	<table border="0"> <tr> <td style="padding-right: 10px;"><i>Standard colors and bases</i></td> <td rowspan="2" style="font-size: 2em; vertical-align: middle;">}</td> <td>– Min. 50° F</td> </tr> <tr> <td></td> <td>– Max. 90° F</td> </tr> <tr> <td></td> <td rowspan="2" style="font-size: 2em; vertical-align: middle;">}</td> <td>– Min. 35° F</td> </tr> <tr> <td style="padding-right: 10px;"><i>Low-temp colors</i></td> <td>– Max. 90° F</td> </tr> </table>	<i>Standard colors and bases</i>	}	– Min. 50° F		– Max. 90° F		}	– Min. 35° F	<i>Low-temp colors</i>	– Max. 90° F																																														
<i>Standard colors and bases</i>	}	– Min. 50° F																																																							
		– Max. 90° F																																																							
	}	– Min. 35° F																																																							
<i>Low-temp colors</i>		– Max. 90° F																																																							
Thin With	Clean Water																																																								
Clean Up Thinner	Clean Water																																																								
Weight Per Gallon <sup>o</sup>	11.0 lbs.																																																								
Storage Temperature – Min.	40° F																																																								
– Max.	90° F																																																								
<b>Volatile Organic Compounds (VOC)</b> <i>Unthinned, this product is formulated not to exceed 250 Grams/Liter. **</i>																																																									

3. **Low Lustre Fortified Acrylic House Paint, Benjamin Moore MoorGard 103 or Equal.** Premium quality, acrylic containing low luster paint fortified with alkyd resin. Soap and water clean up. Mildew resistant. Resistant to fading, cracking, peeling, blistering, dirt pick-up, alkali and fumes.

**Product Information**

**Colors: —Standard:**

Country Redwood 23, Hamilton Blue 36, Tudor Brown 62, Black 80

**—Low Temperature:**

Brilliant White 01, Cottage Red 22, Richmond Bisque 54, Charleston Brown 86, Platinum Gray 71, Navajo White 72, Briarwood 73, Cliffside Gray 74, Montgomery White 76, Sailcloth 77, Lancaster White 78, Charcoal Slate 86

**—Tint Bases:**

Benjamin Moore® Color Preview® bases 3B & 4B

**—Low Temperature Tint Bases:**

Benjamin Moore® Color Preview® bases 1B & 2B

**—Special Colors:**

Contact your Benjamin Moore & Co. representative

**Certification:**

Formulated without lead or mercury

**Federal Specifications Generic Equivalent**

TT-P-96-D, TT-P-55-B

**Technical Assistance**

Available through your local authorized independent Benjamin Moore & Co. dealer. For the location of the dealer nearest you, call 1-800-826-2623, see [www.benjaminmoore.com](http://www.benjaminmoore.com), or consult your local Yellow Pages.

**Technical Data**

**Brilliant White**

Vehicle Type Acrylic Modified Latex

Pigment Type<sup>o</sup> Titanium Dioxide

Volume Solids<sup>o</sup> 42%

Theoretical Coverage At Recommended Film Thickness 400 – 450 Sq. Ft.

Recommended Film Thickness – Wet 3.8 mils

– Dry 1.6 mils

Dry Time @ 77° F — Set To Touch 2 Hours

(25° C) @ 50% RH — To Handle 4 Hours

— To Recoat 4 Hours

— To Service Overnight

*High humidity or cooler temperatures may prolong drying time*

Dries By Evaporation, Coalescence

Viscosity<sup>o</sup> 100 ± 2 KU

Flash Point (Seta) None

60° Specular Gloss Low Lustre

Surface Standard colors { – Min. 50° F

Temperature and bases { – Max. 90° F

at application Low-temp colors { – Min. 35° F

and bases { – Max. 90° F

Thin With Clean Water

Clean Up Thinner Clean Water

Weight Per Gallon<sup>o</sup> 11.4 lbs.

Storage Temperature – Min. 40° F

– Max. 90° F

Volatile Organic Compounds (VOC)

*Unthinned, this product is formulated not to exceed 100 Grams/Liter. \*\**

TD5103B

4. **Flat Fortified Acrylic House Paint, MoorLife 105 or Equal.** Premium quality, acrylic containing flat paint fortified with alkyd resin. Soap and water clean up. Mildew resistant. Resistant to fading, cracking, peeling, blistering, dirt pick-up, alkali and fumes.

<b>Product Information</b>																																																													
<p><b>Colors: —Standard:</b> Country Redwood 23, Tudor Brown 62</p> <p><b>—Low Temperature:</b> Brilliant White 01, Lancaster White 78, Red Brick 21, Hamilton Blue 36, Sandstone 53, Richmond Blsque 54, Brownstone 65, Charleston Brown 66, Annapolis Gray 70, Platinum Gray 71, Navajo White 72, Briarwood 73, Cliffside Gray 74, Limestone 75, Montgomery White 76, Sailcloth 77</p> <p><b>—Tint Bases:</b> Benjamin Moore® Color Preview® bases 3B &amp; 4B</p> <p><b>—Low Temperature Tint Bases:</b> Benjamin Moore® Color Preview® bases 1B &amp; 2B</p> <p><b>—Special Colors:</b> Contact your Benjamin Moore &amp; Co. representative</p> <p><b>Certification:</b> Formulated without lead or mercury</p> <p><b>Federal Specifications Generic Equivalent</b> Exterior: TT-P-001984</p> <p><b>Technical Assistance</b> Available through your local authorized independent Benjamin Moore &amp; Co. dealer. For the location of the dealer nearest you, call 1-800-826-2623, see <a href="http://www.benjaminmoore.com">www.benjaminmoore.com</a>, or consult your local Yellow Pages.</p>	<table border="1"> <thead> <tr> <th style="text-align: left;"><b>Technical Data</b></th> <th style="text-align: left;"><b>Brilliant White</b></th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td>Acrylic Modified Latex</td> </tr> <tr> <td>Pigment Type<sup>o</sup></td> <td>Titanium Dioxide</td> </tr> <tr> <td>Volume Solids<sup>o</sup></td> <td>40%</td> </tr> <tr> <td>Theoretical Coverage At Recommended Film Thickness</td> <td>300 – 400 Sq. Ft.</td> </tr> <tr> <td>Recommended Film Thickness – Wet</td> <td>4.6 mils</td> </tr> <tr> <td>– Dry</td> <td>1.8 mils</td> </tr> <tr> <td>Dry Time @ 77° F — Set To Touch (25° C) @ 50% RH</td> <td>2 – 4 Hours</td> </tr> <tr> <td>– To Handle</td> <td>4 Hours</td> </tr> <tr> <td>– To Recoat</td> <td>4 Hours</td> </tr> <tr> <td>– To Service</td> <td>Overnight</td> </tr> <tr> <td colspan="2"><i>High humidity or cooler temperatures may prolong drying time</i></td> </tr> <tr> <td>Dries By</td> <td>Evaporation, Coalescence</td> </tr> <tr> <td>Viscosity<sup>o</sup></td> <td>100 ± 2 KU</td> </tr> <tr> <td>Flash Point (Seta)</td> <td>None</td> </tr> <tr> <td>60° Specular Gloss</td> <td>Flat</td> </tr> <tr> <td>Surface Temperature at application</td> <td> <table border="0"> <tr> <td>Standard colors and bases</td> <td rowspan="2" style="font-size: 2em;">}</td> <td>– Min.</td> <td>50° F</td> </tr> <tr> <td></td> <td>– Max.</td> <td>90° F</td> </tr> <tr> <td>Low-temp colors and bases</td> <td rowspan="2" style="font-size: 2em;">}</td> <td>– Min.</td> <td>35° F</td> </tr> <tr> <td></td> <td>– Max.</td> <td>90° F</td> </tr> </table> </td> </tr> <tr> <td>Thin With</td> <td>Clean Water</td> </tr> <tr> <td>Clean Up Thinner</td> <td>Clean Water</td> </tr> <tr> <td>Weight Per Gallon<sup>o</sup></td> <td>11.8 lbs.</td> </tr> <tr> <td>Storage Temperature – Min.</td> <td>40° F</td> </tr> <tr> <td>– Max.</td> <td>90° F</td> </tr> <tr> <td colspan="2"> <b>Volatile Organic Compounds (VOC)</b>  <i>Unthinned, this product is formulated not to exceed 100 Grams/Liter.**</i> </td> </tr> </tbody> </table>	<b>Technical Data</b>	<b>Brilliant White</b>	Vehicle Type	Acrylic Modified Latex	Pigment Type <sup>o</sup>	Titanium Dioxide	Volume Solids <sup>o</sup>	40%	Theoretical Coverage At Recommended Film Thickness	300 – 400 Sq. Ft.	Recommended Film Thickness – Wet	4.6 mils	– Dry	1.8 mils	Dry Time @ 77° F — Set To Touch (25° C) @ 50% RH	2 – 4 Hours	– To Handle	4 Hours	– To Recoat	4 Hours	– To Service	Overnight	<i>High humidity or cooler temperatures may prolong drying time</i>		Dries By	Evaporation, Coalescence	Viscosity <sup>o</sup>	100 ± 2 KU	Flash Point (Seta)	None	60° Specular Gloss	Flat	Surface Temperature at application	<table border="0"> <tr> <td>Standard colors and bases</td> <td rowspan="2" style="font-size: 2em;">}</td> <td>– Min.</td> <td>50° F</td> </tr> <tr> <td></td> <td>– Max.</td> <td>90° F</td> </tr> <tr> <td>Low-temp colors and bases</td> <td rowspan="2" style="font-size: 2em;">}</td> <td>– Min.</td> <td>35° F</td> </tr> <tr> <td></td> <td>– Max.</td> <td>90° F</td> </tr> </table>	Standard colors and bases	}	– Min.	50° F		– Max.	90° F	Low-temp colors and bases	}	– Min.	35° F		– Max.	90° F	Thin With	Clean Water	Clean Up Thinner	Clean Water	Weight Per Gallon <sup>o</sup>	11.8 lbs.	Storage Temperature – Min.	40° F	– Max.	90° F	<b>Volatile Organic Compounds (VOC)</b> <i>Unthinned, this product is formulated not to exceed 100 Grams/Liter.**</i>	
<b>Technical Data</b>	<b>Brilliant White</b>																																																												
Vehicle Type	Acrylic Modified Latex																																																												
Pigment Type <sup>o</sup>	Titanium Dioxide																																																												
Volume Solids <sup>o</sup>	40%																																																												
Theoretical Coverage At Recommended Film Thickness	300 – 400 Sq. Ft.																																																												
Recommended Film Thickness – Wet	4.6 mils																																																												
– Dry	1.8 mils																																																												
Dry Time @ 77° F — Set To Touch (25° C) @ 50% RH	2 – 4 Hours																																																												
– To Handle	4 Hours																																																												
– To Recoat	4 Hours																																																												
– To Service	Overnight																																																												
<i>High humidity or cooler temperatures may prolong drying time</i>																																																													
Dries By	Evaporation, Coalescence																																																												
Viscosity <sup>o</sup>	100 ± 2 KU																																																												
Flash Point (Seta)	None																																																												
60° Specular Gloss	Flat																																																												
Surface Temperature at application	<table border="0"> <tr> <td>Standard colors and bases</td> <td rowspan="2" style="font-size: 2em;">}</td> <td>– Min.</td> <td>50° F</td> </tr> <tr> <td></td> <td>– Max.</td> <td>90° F</td> </tr> <tr> <td>Low-temp colors and bases</td> <td rowspan="2" style="font-size: 2em;">}</td> <td>– Min.</td> <td>35° F</td> </tr> <tr> <td></td> <td>– Max.</td> <td>90° F</td> </tr> </table>	Standard colors and bases	}	– Min.	50° F		– Max.	90° F	Low-temp colors and bases	}	– Min.	35° F		– Max.	90° F																																														
Standard colors and bases	}	– Min.		50° F																																																									
		– Max.	90° F																																																										
Low-temp colors and bases	}	– Min.	35° F																																																										
		– Max.	90° F																																																										
Thin With	Clean Water																																																												
Clean Up Thinner	Clean Water																																																												
Weight Per Gallon <sup>o</sup>	11.8 lbs.																																																												
Storage Temperature – Min.	40° F																																																												
– Max.	90° F																																																												
<b>Volatile Organic Compounds (VOC)</b> <i>Unthinned, this product is formulated not to exceed 100 Grams/Liter.**</i>																																																													

5. Flat Finish Wall Satin, Benjamin Moore 215 or equal. Premium quality, proprietary latex coat in with optimal scrubability in a flat finish coupled with a spatter resistant formula to minimize roller "overspray". Soap and water cleanup

**Product Information**

**Colors: —Standard:**

White and a variety of ready-mixed colors

**—Tint Bases:**

Benjamin Moore & Co. Color Preview® bases 1B, 2B, 3B, and 4B

**—Special Colors:**

Contact your Benjamin Moore & Co. representative

**Certification:**

Master Painters Institute MPI #53  
Formulated without lead, mercury, or chromates.  
Very low in VOCs.

**Federal Specifications Generic Equivalent:**

TT-P-29-J

**Technical Assistance**

Available through your local authorized independent Benjamin Moore & Co. dealer. For the location of the dealer nearest you, call 1-800-826-2623, see [www.benjaminmoore.com](http://www.benjaminmoore.com), or consult your local Yellow Pages.

**Technical Data**

**White**

Vehicle Type	Proprietary Acrylic Latex
Pigment Type <sup>o</sup>	Titanium Dioxide
Volume Solids <sup>o</sup>	33%
Theoretical Coverage At Recommended Film Thickness	400 – 450 Sq. Ft.
Recommended Film Thickness – Wet	3.8 mils
– Dry	1.3 mils
Dry Time @ 77° F — Set To Touch	1 Hour
(25° C) @ 50% RH — Dry To Touch	1 Hour
— To Recoat	1 to 2 Hours
— To Hard Dry	24 Hours
Dries By	Evaporation, Coalescence
Viscosity <sup>o</sup>	93 ± 3 KU
Flash Point (Seta)	None
60° Specular Gloss	Flat
Surface Temperature at application – Min.	50° F
– Max.	90° F
Thin With	Clean Water
Clean Up Thinner	Clean Water
Weight Per Gallon <sup>o</sup>	10.9 lbs.
Storage Temperature – Min.	40° F
– Max.	90° F

Volatile Organic Compounds (VOC)  
Unthinned, this product is formulated  
not to exceed 100 Grams/Liter. \*\*

6. Interior Latex Eggshell AquaVelvet, Benjamin Moore 319 or equal. Premium quality, proprietary latex coating eggshell finish with washability of a semi-gloss.

Product Information																																															
<p><b>Colors: —Standard:</b> White and a range of ready-mixed off-white colors coordinated with Moore's® Satin Impervo® (235), Regal® Wall Satin® (215), Regal® AquaPearl® (310), and Regal® AquaGlo® (333)</p> <p style="text-align: center;"><b>—Tint Bases:</b> Benjamin Moore &amp; Co. Color Preview® bases 1B, 2B, 3B, &amp; 4B</p> <p style="text-align: center;"><b>—Special Colors:</b> Contact your Benjamin Moore &amp; Co. representative</p> <p><b>Certification:</b> Formulated without lead or mercury. Very low in VOCs.</p> <p><b>Federal Specifications Generic Equivalent:</b> TT-P-2119</p> <p><b>Technical Assistance</b> Available through your local authorized independent Benjamin Moore &amp; Co. dealer. For the location of the dealer nearest you, call 1-800-828-2623, see <a href="http://www.benjaminmoore.com">www.benjaminmoore.com</a>, or consult your local Yellow Pages.</p>	<table border="1"> <thead> <tr> <th style="text-align: left;"><b>Technical Data</b></th> <th style="text-align: right;"><b>White</b></th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td style="text-align: right;">Proprietary Latex</td> </tr> <tr> <td>Pigment Type<sup>o</sup></td> <td style="text-align: right;">Titanium Dioxide</td> </tr> <tr> <td>Volume Solids<sup>o</sup></td> <td style="text-align: right;">37%</td> </tr> <tr> <td>Theoretical Coverage At Recommended Film Thickness</td> <td style="text-align: right;">400 – 450 Sq. Ft.</td> </tr> <tr> <td>Recommended Film Thickness – Wet</td> <td style="text-align: right;">3.8 mils</td> </tr> <tr> <td style="text-align: right;">– Dry</td> <td style="text-align: right;">1.4 mils</td> </tr> <tr> <td>Dry Time @ 77° F — Set To Touch</td> <td style="text-align: right;">2 Hours</td> </tr> <tr> <td>(25° C) @ 50% RH — To Handle</td> <td style="text-align: right;">2 Hours</td> </tr> <tr> <td style="text-align: right;">– To Recoat</td> <td style="text-align: right;">4 Hours</td> </tr> <tr> <td style="text-align: right;">– To Service</td> <td style="text-align: right;">24 Hours</td> </tr> <tr> <td>Dries By</td> <td style="text-align: right;">Evaporation, Coalescence</td> </tr> <tr> <td>Viscosity<sup>o</sup></td> <td style="text-align: right;">90 ± 2 KU</td> </tr> <tr> <td>Flash Point (Seta)</td> <td style="text-align: right;">None</td> </tr> <tr> <td>60° Specular Gloss</td> <td style="text-align: right;">Eggshell</td> </tr> <tr> <td>Surface Temperature at application – Min.</td> <td style="text-align: right;">50° F</td> </tr> <tr> <td style="text-align: right;">– Max.</td> <td style="text-align: right;">90° F</td> </tr> <tr> <td>Thin With</td> <td style="text-align: right;">Clean Water</td> </tr> <tr> <td>Clean Up Thinner</td> <td style="text-align: right;">Clean Water</td> </tr> <tr> <td>Weight Per Gallon<sup>o</sup></td> <td style="text-align: right;">11.2 lbs.</td> </tr> <tr> <td>Storage Temperature – Min.</td> <td style="text-align: right;">40° F</td> </tr> <tr> <td style="text-align: right;">– Max.</td> <td style="text-align: right;">90° F</td> </tr> <tr> <td colspan="2">           Volatile Organic Compounds (VOC)  <i>Unthinned, this product is formulated not to exceed 250 Grams/Liter. **</i> </td> </tr> </tbody> </table>	<b>Technical Data</b>	<b>White</b>	Vehicle Type	Proprietary Latex	Pigment Type <sup>o</sup>	Titanium Dioxide	Volume Solids <sup>o</sup>	37%	Theoretical Coverage At Recommended Film Thickness	400 – 450 Sq. Ft.	Recommended Film Thickness – Wet	3.8 mils	– Dry	1.4 mils	Dry Time @ 77° F — Set To Touch	2 Hours	(25° C) @ 50% RH — To Handle	2 Hours	– To Recoat	4 Hours	– To Service	24 Hours	Dries By	Evaporation, Coalescence	Viscosity <sup>o</sup>	90 ± 2 KU	Flash Point (Seta)	None	60° Specular Gloss	Eggshell	Surface Temperature at application – Min.	50° F	– Max.	90° F	Thin With	Clean Water	Clean Up Thinner	Clean Water	Weight Per Gallon <sup>o</sup>	11.2 lbs.	Storage Temperature – Min.	40° F	– Max.	90° F	Volatile Organic Compounds (VOC) <i>Unthinned, this product is formulated not to exceed 250 Grams/Liter. **</i>	
<b>Technical Data</b>	<b>White</b>																																														
Vehicle Type	Proprietary Latex																																														
Pigment Type <sup>o</sup>	Titanium Dioxide																																														
Volume Solids <sup>o</sup>	37%																																														
Theoretical Coverage At Recommended Film Thickness	400 – 450 Sq. Ft.																																														
Recommended Film Thickness – Wet	3.8 mils																																														
– Dry	1.4 mils																																														
Dry Time @ 77° F — Set To Touch	2 Hours																																														
(25° C) @ 50% RH — To Handle	2 Hours																																														
– To Recoat	4 Hours																																														
– To Service	24 Hours																																														
Dries By	Evaporation, Coalescence																																														
Viscosity <sup>o</sup>	90 ± 2 KU																																														
Flash Point (Seta)	None																																														
60° Specular Gloss	Eggshell																																														
Surface Temperature at application – Min.	50° F																																														
– Max.	90° F																																														
Thin With	Clean Water																																														
Clean Up Thinner	Clean Water																																														
Weight Per Gallon <sup>o</sup>	11.2 lbs.																																														
Storage Temperature – Min.	40° F																																														
– Max.	90° F																																														
Volatile Organic Compounds (VOC) <i>Unthinned, this product is formulated not to exceed 250 Grams/Liter. **</i>																																															

7. Interior Semi-Gloss, Benjamin Moore AquaGlo 333 or equal. Splatter resistant latex semi-gloss enamel. Washable and scrubbable.

**Product Information**

**Colors: —Standard:**

White, Black, and a range of ready-mixed off-white colors coordinated with Moore's® Satin Impervo® (235), Regal Wall Satin® (215), Regal AquaPearl® (310), and Regal AquaVelvet® (319)

**—Tint Bases:**

Benjamin Moore & Co. Color Preview® bases 1B, 2B, 3B, and 4B

**—Special Colors:**

Contact your Benjamin Moore & Co. representative

**Certification:**

Formulated without lead or mercury.  
Very low in VOCs.

**Federal Specifications Generic Equivalent:**

TT-P-1511-B

**Technical Assistance**

Available through your local authorized independent Benjamin Moore & Co. dealer. For the location of the dealer nearest you, call 1-800-826-2623, see [www.benjaminmoore.com](http://www.benjaminmoore.com), or consult your local Yellow Pages.

**Technical Data**

**White**

Vehicle Type	Proprietary Latex
Pigment Type <sup>o</sup>	Titanium Dioxide
Volume Solids <sup>o</sup>	34%
Theoretical Coverage At Recommended Film Thickness	400 – 450 Sq. Ft.
Recommended Film Thickness – Wet	3.8 mils
– Dry	1.3 mils
Dry Time @ 77° F — Set To Touch	2 Hours
(25° C) @ 50% RH — To Handle	4 Hours
— To Recoat	12 Hours
— To Service	24 Hours
Dries By	Evaporation, Coalescence
Viscosity <sup>o</sup>	86 ± 1 KU
Flash Point (Seta)	None
60° Specular Gloss	Semi-Gloss
Surface Temperature at application – Min.	50° F
– Max.	90° F
Thin With	Clean Water
Clean Up Thinner	Clean Water
Weight Per Gallon <sup>o</sup>	10.2 lbs.
Storage Temperature – Min.	40° F
– Max.	90° F

Volatile Organic Compounds (VOC)  
Unthinned, this product is formulated  
not to exceed 380 Grams/Liter. \*\*

8. Interior Latex Primer, Benjamin Moore Super Craft 250 or equal. Fast drying, acrylic latex primer and sealer.

**Product Information**

**Colors: —Standard:**

250 00 White  
(May be tinted with up to 2.0 fl. oz. of Benjamin Moore & Co. Color Preview® colorants per gallon.)

**—Tint Bases:**

Not available

**—Special Colors:**

Contact your Benjamin Moore & Co. representative

**Certification:**

Formulated without lead, mercury, or chromates.

**Federal Specifications Generic Equivalent**

TT-P-650C

**Technical Assistance**

Available through your local authorized independent Benjamin Moore & Co. dealer.  
For the location of the dealer nearest you, call 1-800-826-2623, see [www.benjaminmoore.com](http://www.benjaminmoore.com), or consult your local Yellow Pages.

**Technical Data**

**White**

Vehicle Type	Acrylic Blended Latex
Pigment Type	Titanium Dioxide
Volume Solids	20%
Theoretical Coverage At Recommended Film Thickness	400-450 Sq. Ft.
Recommended Film Thickness – Wet	3.8 Mills
– Dry	0.8 Mills
Dry Time @ 77° F — Set To Touch	1 Hour
(25° C) @ 50% RH — To Recoat	1–2 Hours
– To Hard Dry	4 Hours
Dries By	Evaporation, Coalescence
Viscosity	103 ± 3 KU
Flash Point (Seta)	None
60° Specular Gloss	2%
85° Specular Gloss	1%
Surface Temperature at application – Min.	50° F
– Max.	90° F
Thin With:	Clean Water
Clean Up Thinner	Clean Water
Weight Per Gallon	10.1 lbs.
Storage Temperature – Min.	40° F
– Max.	90° F

Volatile Organic Compounds (VOC)  
Unthinned, this product is formulated not to exceed 200 Grams/Liter\*\*

9. Interior Latex Eggshell Enamel, Benjamin Moore Super Craft 251 or equal. Fast drying, durable coating with appearance of eggshell finish yet may be washed like a semi-gloss enamel.

**Product Information**

**Colors: —Standard:**  
251 01 White

**—Tint Bases:**  
251 90 Tintable White  
(May be tinted with up to 2.0 fl. oz. of Benjamin Moore & Co. Color Preview<sup>®</sup> colorants per gallon.)

**—Special Colors:**  
Contact your Benjamin Moore & Co. representative

**Certification:**  
Formulated without lead, mercury, or chromates.

**Federal Specifications Generic Equivalent**  
TT-P-2119

**Technical Assistance**  
Available through your local authorized independent Benjamin Moore & Co. dealer.  
For the location of the dealer nearest you, call 1-800-826-2623, see [www.benjaminmoore.com](http://www.benjaminmoore.com), or consult your local Yellow Pages.

<b>Technical Data</b>	<b>White</b>
Vehicle Type	Acrylic Blended Latex
Pigment Type <sup>0</sup>	Titanium Dioxide
Volume Solids <sup>0</sup>	30%
Theoretical Coverage At Recommended Film Thickness	400-450 Sq. Ft.
Recommended Film Thickness – Wet	3.8 Mills
– Dry	1.1 Mills
Dry Time @ 77° F — Dry To Touch	2 Hours
(25° C) @ 50% RH — To Recoat	4 Hours
— To Hard Dry	24 Hours
Dries By	Evaporation, Coalescence
Viscosity <sup>0</sup>	100 ± 3 KU
Flash Point (Seta)	None
60° Specular Gloss	4.5 ± 3%
85° Specular Gloss	12 ± 3%
Surface Temperature at application – Min.	50° F
– Max.	90° F
Thin With:	Clean Water
Clean Up Thinner	Clean Water
Weight Per Gallon <sup>0</sup>	10.65 lbs.
Storage Temperature – Min.	40° F
– Max.	90° F
Volatile Organic Compounds (VOC) Unthinned, this product is formulated not to exceed 150 Grams/Liter**	

10. **Latex Semi-Gloss Enamel, Benjamin Moore Super Craft 252 or Equal.** Durable semi-gloss latex enamel for interior trim, doors, walls and ceilings. Soil-resistant, washable and durable.

Product Information																																													
<p><b>Colors: —Standard:</b> 252 01 White (May be tinted with up to 2.0 fl. oz. of Benjamin Moore &amp; Co. Color Preview® colorants per gallon.)</p> <p style="text-align: center;"><b>—Tint Bases:</b> 252 90 Tintable White (May be tinted with up to 2.0 fl. oz. of Benjamin Moore &amp; Co. Color Preview® colorants per gallon.)</p> <p style="text-align: center;"><b>—Special Colors:</b> Contact your Benjamin Moore &amp; Co. representative</p> <p><b>Certification:</b> Formulated without lead, mercury, or chromates.</p> <p><b>Federal Specifications Generic Equivalent</b> TT-P-1511B</p> <p><b>Technical Assistance</b> Available through your local authorized independent Benjamin Moore &amp; Co. dealer. For the location of the dealer nearest you, call 1-800-826-2623, see <a href="http://www.benjaminmoore.com">www.benjaminmoore.com</a>, or consult your local Yellow Pages.</p>	<table border="1"> <thead> <tr> <th style="text-align: left;">Technical Data</th> <th style="text-align: right;">White</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td style="text-align: right;">Acrylic Blended Latex</td> </tr> <tr> <td>Pigment Type<sup>o</sup></td> <td style="text-align: right;">Titanium Dioxide</td> </tr> <tr> <td>Volume Solids<sup>o</sup></td> <td style="text-align: right;">24%</td> </tr> <tr> <td>Theoretical Coverage At Recommended Film Thickness</td> <td style="text-align: right;">400-450 Sq. Ft.</td> </tr> <tr> <td>Recommended Film Thickness – Wet</td> <td style="text-align: right;">3.8 Mils</td> </tr> <tr> <td style="text-align: right;">– Dry</td> <td style="text-align: right;">1.0 Mils</td> </tr> <tr> <td>Dry Time @ 77° F — Dry To Touch</td> <td style="text-align: right;">2 Hours</td> </tr> <tr> <td>(25° C) @ 50% RH — To Recoat</td> <td style="text-align: right;">Overnight</td> </tr> <tr> <td style="text-align: right;">– To Hard Dry</td> <td style="text-align: right;">24 Hours</td> </tr> <tr> <td>Dries By</td> <td style="text-align: right;">Evaporation, Coalescence</td> </tr> <tr> <td>Viscosity<sup>o</sup></td> <td style="text-align: right;">100 ± 3 KU</td> </tr> <tr> <td>Flash Point (Seta)</td> <td style="text-align: right;">None</td> </tr> <tr> <td>60° Specular Gloss</td> <td style="text-align: right;">40 – 55%</td> </tr> <tr> <td>Surface Temperature at application – Min.</td> <td style="text-align: right;">50° F</td> </tr> <tr> <td style="text-align: right;">– Max.</td> <td style="text-align: right;">90° F</td> </tr> <tr> <td>Thin With:</td> <td style="text-align: right;">Clean Water</td> </tr> <tr> <td>Clean Up Thinner</td> <td style="text-align: right;">Clean Water</td> </tr> <tr> <td>Weight Per Gallon<sup>o</sup></td> <td style="text-align: right;">9.78 lbs.</td> </tr> <tr> <td>Storage Temperature – Min.</td> <td style="text-align: right;">40° F</td> </tr> <tr> <td style="text-align: right;">– Max.</td> <td style="text-align: right;">90° F</td> </tr> <tr> <td colspan="2">           Volatile Organic Compounds (VOC)  <i>Unthinned, this product is formulated not to exceed 150 Grams/Liter**</i> </td> </tr> </tbody> </table>	Technical Data	White	Vehicle Type	Acrylic Blended Latex	Pigment Type <sup>o</sup>	Titanium Dioxide	Volume Solids <sup>o</sup>	24%	Theoretical Coverage At Recommended Film Thickness	400-450 Sq. Ft.	Recommended Film Thickness – Wet	3.8 Mils	– Dry	1.0 Mils	Dry Time @ 77° F — Dry To Touch	2 Hours	(25° C) @ 50% RH — To Recoat	Overnight	– To Hard Dry	24 Hours	Dries By	Evaporation, Coalescence	Viscosity <sup>o</sup>	100 ± 3 KU	Flash Point (Seta)	None	60° Specular Gloss	40 – 55%	Surface Temperature at application – Min.	50° F	– Max.	90° F	Thin With:	Clean Water	Clean Up Thinner	Clean Water	Weight Per Gallon <sup>o</sup>	9.78 lbs.	Storage Temperature – Min.	40° F	– Max.	90° F	Volatile Organic Compounds (VOC) <i>Unthinned, this product is formulated not to exceed 150 Grams/Liter**</i>	
Technical Data	White																																												
Vehicle Type	Acrylic Blended Latex																																												
Pigment Type <sup>o</sup>	Titanium Dioxide																																												
Volume Solids <sup>o</sup>	24%																																												
Theoretical Coverage At Recommended Film Thickness	400-450 Sq. Ft.																																												
Recommended Film Thickness – Wet	3.8 Mils																																												
– Dry	1.0 Mils																																												
Dry Time @ 77° F — Dry To Touch	2 Hours																																												
(25° C) @ 50% RH — To Recoat	Overnight																																												
– To Hard Dry	24 Hours																																												
Dries By	Evaporation, Coalescence																																												
Viscosity <sup>o</sup>	100 ± 3 KU																																												
Flash Point (Seta)	None																																												
60° Specular Gloss	40 – 55%																																												
Surface Temperature at application – Min.	50° F																																												
– Max.	90° F																																												
Thin With:	Clean Water																																												
Clean Up Thinner	Clean Water																																												
Weight Per Gallon <sup>o</sup>	9.78 lbs.																																												
Storage Temperature – Min.	40° F																																												
– Max.	90° F																																												
Volatile Organic Compounds (VOC) <i>Unthinned, this product is formulated not to exceed 150 Grams/Liter**</i>																																													

11. **Latex Flat, Benjamin Moore Super Hide 282 or equal.** Acrylic blended latex flat enamel coating. Washable.

<b>Product Information</b>																																					
<p><b>Colors: —Standard:</b> White and a selection of standard colors. (White and Off-whites may be tinted with up to 2.0 fl. oz. of Benjamin Moore &amp; Co. Color Preview® colorants per gallon.)</p> <p style="text-align: center;"><b>—Tint Bases:</b> Benjamin Moore &amp; Co. Color Preview® bases 1B, 2B, 3B, &amp; 4B</p> <p style="text-align: center;"><b>—Special Colors:</b> Contact your Benjamin Moore &amp; Co. representative</p> <p><b>Certification:</b> Formulated without lead, mercury, or chromates.</p> <p><b>Federal Specifications Generic Equivalent</b> TT-P-29-J</p> <p><b>Technical Assistance</b> Available through your local authorized independent Benjamin Moore &amp; Co. dealer. For the location of the dealer nearest you, call 1-800-826-2623, see <a href="http://www.benjaminmoore.com">www.benjaminmoore.com</a>, or consult your local Yellow pages.</p>	<table border="1"> <thead> <tr> <th style="text-align: left;"><b>Technical Data</b></th> <th style="text-align: right;"><b>White</b></th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td style="text-align: right;">Acrylic Blended Latex</td> </tr> <tr> <td>Pigment Type°</td> <td style="text-align: right;">Titanium Dioxide</td> </tr> <tr> <td>Volume Solids°</td> <td style="text-align: right;">25%</td> </tr> <tr> <td>Theoretical Coverage At Recommended Film Thickness</td> <td style="text-align: right;">400-450 Sq. Ft.</td> </tr> <tr> <td colspan="2" style="text-align: center;"><i>Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.</i></td> </tr> <tr> <td>Recommended Film Thickness – Wet – Dry</td> <td style="text-align: right;">3.8 Mills 1.0 Mills</td> </tr> <tr> <td>Dry Time @ 77° F — Dry To Touch (25° C) @ 50% RH — To Recoat – To Hard Dry</td> <td style="text-align: right;">1 Hour 2-3 Hours 4-6 Hours</td> </tr> <tr> <td>Dries By</td> <td style="text-align: right;">Evaporation, Coalescence</td> </tr> <tr> <td>Viscosity°</td> <td style="text-align: right;">110 ± 3 KU</td> </tr> <tr> <td>Flash Point (Seta)</td> <td style="text-align: right;">None</td> </tr> <tr> <td>60° Specular Gloss</td> <td style="text-align: right;">Flat</td> </tr> <tr> <td>Surface Temperature at application – Min. – Max.</td> <td style="text-align: right;">50° F 90° F</td> </tr> <tr> <td>Thin With:</td> <td style="text-align: right;">Clean Water</td> </tr> <tr> <td>Clean Up Thinner</td> <td style="text-align: right;">Clean Water</td> </tr> <tr> <td>Weight Per Gallon°</td> <td style="text-align: right;">10.8 lb.</td> </tr> <tr> <td>Storage Temperature – Min. – Max.</td> <td style="text-align: right;">40° F 90° F</td> </tr> <tr> <td colspan="2">Volatile Organic Compounds (VOC) <i>Unthinned, this product is formulated not to exceed 100 Grams/Liter**</i></td> </tr> </tbody> </table>	<b>Technical Data</b>	<b>White</b>	Vehicle Type	Acrylic Blended Latex	Pigment Type°	Titanium Dioxide	Volume Solids°	25%	Theoretical Coverage At Recommended Film Thickness	400-450 Sq. Ft.	<i>Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.</i>		Recommended Film Thickness – Wet – Dry	3.8 Mills 1.0 Mills	Dry Time @ 77° F — Dry To Touch (25° C) @ 50% RH — To Recoat – To Hard Dry	1 Hour 2-3 Hours 4-6 Hours	Dries By	Evaporation, Coalescence	Viscosity°	110 ± 3 KU	Flash Point (Seta)	None	60° Specular Gloss	Flat	Surface Temperature at application – Min. – Max.	50° F 90° F	Thin With:	Clean Water	Clean Up Thinner	Clean Water	Weight Per Gallon°	10.8 lb.	Storage Temperature – Min. – Max.	40° F 90° F	Volatile Organic Compounds (VOC) <i>Unthinned, this product is formulated not to exceed 100 Grams/Liter**</i>	
<b>Technical Data</b>	<b>White</b>																																				
Vehicle Type	Acrylic Blended Latex																																				
Pigment Type°	Titanium Dioxide																																				
Volume Solids°	25%																																				
Theoretical Coverage At Recommended Film Thickness	400-450 Sq. Ft.																																				
<i>Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.</i>																																					
Recommended Film Thickness – Wet – Dry	3.8 Mills 1.0 Mills																																				
Dry Time @ 77° F — Dry To Touch (25° C) @ 50% RH — To Recoat – To Hard Dry	1 Hour 2-3 Hours 4-6 Hours																																				
Dries By	Evaporation, Coalescence																																				
Viscosity°	110 ± 3 KU																																				
Flash Point (Seta)	None																																				
60° Specular Gloss	Flat																																				
Surface Temperature at application – Min. – Max.	50° F 90° F																																				
Thin With:	Clean Water																																				
Clean Up Thinner	Clean Water																																				
Weight Per Gallon°	10.8 lb.																																				
Storage Temperature – Min. – Max.	40° F 90° F																																				
Volatile Organic Compounds (VOC) <i>Unthinned, this product is formulated not to exceed 100 Grams/Liter**</i>																																					

12. **Latex Semi-Gloss Enamel, Benjamin Moore Super Hide 283 or equal.** Acrylic blended latex semi-gloss enamel for interior surfaces. Spatter resistant, soap and water cleanup. Washable.

<b>Product Information</b>																																					
<p><b>Colors: —Standard:</b> White and a selection of standard colors. (White and Off-whites may be tinted with up to 2.0 fl. oz. of Benjamin Moore &amp; Co. Color Preview® colorants per gallon.)</p> <p style="text-align: center;"><b>—Tint Bases:</b> Benjamin Moore &amp; Co. Color Preview® bases 1B, 2B, 3B, &amp; 4B</p> <p style="text-align: center;"><b>—Special Colors:</b> Contact your Benjamin Moore &amp; Co. representative</p> <p><b>Certification:</b> Formulated without lead, mercury, or chromates.</p> <p><b>Federal Specifications Generic Equivalent</b> TT-P-1511-B</p> <p><b>Technical Assistance</b> Available through your local authorized independent Benjamin Moore &amp; Co. dealer. For the location of the dealer nearest you, call 1-800-826-2623, see www.benjaminmoore.com, or consult your local Yellow Pages.</p>	<table border="1"> <thead> <tr> <th style="text-align: left;"><b>Technical Data</b></th> <th style="text-align: right;"><b>White</b></th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td style="text-align: right;">Acrylic Blended Latex</td> </tr> <tr> <td>Pigment Type<sup>o</sup></td> <td style="text-align: right;">Titanium Dioxide</td> </tr> <tr> <td>Volume Solids<sup>o</sup></td> <td style="text-align: right;">27%</td> </tr> <tr> <td>Theoretical Coverage At Recommended Film Thickness</td> <td style="text-align: right;">400-450 Sq. Ft.</td> </tr> <tr> <td colspan="2" style="text-align: center;"><i>Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.</i></td> </tr> <tr> <td>Recommended Film Thickness – Wet – Dry</td> <td style="text-align: right;">3.8 Mils 1.0 Mils</td> </tr> <tr> <td>Dry Time @ 77° F — Dry To Touch (25° C) @ 50% RH — To Recoat – To Hard Dry</td> <td style="text-align: right;">2 Hours 12 Hours Overnight</td> </tr> <tr> <td>Dries By</td> <td style="text-align: right;">Evaporation, Coalescence</td> </tr> <tr> <td>Viscosity<sup>o</sup></td> <td style="text-align: right;">100 ± 1 KU</td> </tr> <tr> <td>Flash Point (Seta)</td> <td style="text-align: right;">None</td> </tr> <tr> <td>60° Specular Gloss</td> <td style="text-align: right;">Semi-Gloss</td> </tr> <tr> <td>Surface Temperature at application – Min. – Max.</td> <td style="text-align: right;">50° F 90° F</td> </tr> <tr> <td>Thin With:</td> <td style="text-align: right;">Clean Water</td> </tr> <tr> <td>Clean Up Thinner</td> <td style="text-align: right;">Waters</td> </tr> <tr> <td>Weight Per Gallon<sup>o</sup></td> <td style="text-align: right;">10.2 lbs.</td> </tr> <tr> <td>Storage Temperature – Min. – Max.</td> <td style="text-align: right;">40° F 90° F</td> </tr> <tr> <td colspan="2">Volatile Organic Compounds (VOC) <i>Unthinned, this product is formulated not to exceed 150 Grams/Liter**</i></td> </tr> </tbody> </table>	<b>Technical Data</b>	<b>White</b>	Vehicle Type	Acrylic Blended Latex	Pigment Type <sup>o</sup>	Titanium Dioxide	Volume Solids <sup>o</sup>	27%	Theoretical Coverage At Recommended Film Thickness	400-450 Sq. Ft.	<i>Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.</i>		Recommended Film Thickness – Wet – Dry	3.8 Mils 1.0 Mils	Dry Time @ 77° F — Dry To Touch (25° C) @ 50% RH — To Recoat – To Hard Dry	2 Hours 12 Hours Overnight	Dries By	Evaporation, Coalescence	Viscosity <sup>o</sup>	100 ± 1 KU	Flash Point (Seta)	None	60° Specular Gloss	Semi-Gloss	Surface Temperature at application – Min. – Max.	50° F 90° F	Thin With:	Clean Water	Clean Up Thinner	Waters	Weight Per Gallon <sup>o</sup>	10.2 lbs.	Storage Temperature – Min. – Max.	40° F 90° F	Volatile Organic Compounds (VOC) <i>Unthinned, this product is formulated not to exceed 150 Grams/Liter**</i>	
<b>Technical Data</b>	<b>White</b>																																				
Vehicle Type	Acrylic Blended Latex																																				
Pigment Type <sup>o</sup>	Titanium Dioxide																																				
Volume Solids <sup>o</sup>	27%																																				
Theoretical Coverage At Recommended Film Thickness	400-450 Sq. Ft.																																				
<i>Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.</i>																																					
Recommended Film Thickness – Wet – Dry	3.8 Mils 1.0 Mils																																				
Dry Time @ 77° F — Dry To Touch (25° C) @ 50% RH — To Recoat – To Hard Dry	2 Hours 12 Hours Overnight																																				
Dries By	Evaporation, Coalescence																																				
Viscosity <sup>o</sup>	100 ± 1 KU																																				
Flash Point (Seta)	None																																				
60° Specular Gloss	Semi-Gloss																																				
Surface Temperature at application – Min. – Max.	50° F 90° F																																				
Thin With:	Clean Water																																				
Clean Up Thinner	Waters																																				
Weight Per Gallon <sup>o</sup>	10.2 lbs.																																				
Storage Temperature – Min. – Max.	40° F 90° F																																				
Volatile Organic Compounds (VOC) <i>Unthinned, this product is formulated not to exceed 150 Grams/Liter**</i>																																					

13. **Latex Primer/Undercoater, Benjamin Moore Super Hide 284 or equal.** Acrylic blended latex primer-undercoater. Spatterproof, quick dry.

**Product Information**

**Colors: —Standard:**

284 00 White  
 (May be tinted with up to 2.0 fl. oz. of  
 Benjamin Moore & Co. Color Preview® colorants per gallon.)

**—Tint Bases:**

Not available

**—Special Colors:**

Contact your Benjamin Moore & Co. representative

**Certification:**

Formulated without lead, mercury, or chromates.

**Federal Specifications Generic Equivalent**

TT-P-650C

**Technical Assistance**

Available through your local authorized independent  
 Benjamin Moore & Co. dealer.  
 For the location of the dealer nearest you, call 1-800-826-2623,  
 see [www.benjaminmoore.com](http://www.benjaminmoore.com), or consult your local Yellow Pages.

**Technical Data**

**White**

Vehicle Type	Acrylic Blended Latex
Pigment Type	Titanium Dioxide
Volume Solids	28%
Theoretical Coverage At Recommended Film Thickness	500-600 Sq. Ft.
<i>Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.</i>	
Recommended Film Thickness – Wet	3.0 Mils
– Dry	0.8 Mils
Dry Time @ 77° F — Set To Touch (25° C) @ 50% RH — To Recoat	½ Hour 1 Hour
– To Hard Dry	4 Hours
Dries By	Evaporation, Coalescence
Viscosity	103 ± 3 KU
Flash Point (Seta)	None
60° Specular Gloss	Flat
Surface Temperature at application – Min.	50° F
– Max.	90° F
Thin With:	Clean Water
Clean Up Thinner	Clean Water
Weight Per Gallon	11.3 lbs.
Storage Temperature – Min.	40° F
– Max.	90° F
Volatile Organic Compounds (VOC) <i>Unthinned, this product is formulated                  not to exceed 200 Grams/Liter**</i>	

14. **Latex Eggshell Enamel Benjamin Moore Super Hide 286 or equal.** Acrylic blended latex eggshell enamel for interior surfaces. Washable, Spatter resistant, soap and water cleanup.

**Product Information**

**Colors: —Standard:**

White (01), Bone White (03), Linen White (70), Navajo White (73), China White (74), and Atrium White (79). Swiss Coffee (11), Cottage White (13), and Frost (14) also available in limited areas. (White and Off-whites may be tinted with up to 2.0 fl. oz. of Benjamin Moore & Co. Color Preview® colorants per gallon.)

**—Tint Bases:**

Benjamin Moore & Co. Color Preview® bases 1B, 2B, 3B, & 4B

**—Special Colors:**

Contact your Benjamin Moore & Co. representative

**Certification:**

Formulated without lead, mercury, or chromates.

**Technical Assistance**

Available through your local authorized independent Benjamin Moore & Co. dealer. For the location of the dealer nearest you, call 1-800-826-2623, see [www.benjaminmoore.com](http://www.benjaminmoore.com), or consult your local Yellow pages.

**Technical Data**

**White**

Vehicle Type	Acrylic Blended Latex
Pigment Type <sup>0</sup>	Titanium Dioxide
Volume Solids <sup>0</sup>	35%
Theoretical Coverage At Recommended Film Thickness	400 – 450 Sq. Ft.
<i>Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.</i>	
Recommended Film Thickness – Wet	4.0 mils
– Dry	1.4 mils
Dry Time @ 77° F — Set To Touch	2 Hours
(25° C) @ 50% RH — To Recoat	4 Hours
– To Hard Dry	24 Hours
Dries By	Evaporation, Coalescence
Viscosity <sup>0</sup>	100 ± 1 KU
Flash Point (Seta)	None
60° Specular Gloss	Eggshell
Surface Temperature at application – Min.	50° F
– Max.	90° F
Thin With:	Clean Water
Clean Up Thinner	Clean Water
Weight Per Gallon <sup>2</sup>	10.7 lbs.
Storage Temperature – Min.	40° F
– Max.	90° F

Volatile Organic Compounds (VOC)  
*Unthinned, this product is formulated not to exceed 150 Grams/Liter\*\**

15. Latex Flat, Benjamin Moore Super Craft 290 or equal. Production quality, acrylic blended latex coating flat finish.

**Product Information**

**Colors: —Standard:**

290 01 White  
(May be tinted with up to 2.0 fl. oz. of Benjamin Moore & Co. Color Preview® colorants per gallon.)

**—Tint Bases:**

290 90 Tintable White  
(May be tinted with up to 2.0 fl. oz. of Benjamin Moore & Co. Color Preview® colorants per gallon.)

**—Special Colors:**

Contact your Benjamin Moore & Co. representative

**Certification:**

Formulated without lead, mercury, or chromates.  
Formulated with non-photochemically reactive solvents.

**Federal Specifications Generic Equivalent**

TT-P-29-J

**Technical Assistance**

Available through your local authorized independent Benjamin Moore & Co. dealer.  
For the location of the dealer nearest you, call 1-800-826-2623, see [www.benjaminmoore.com](http://www.benjaminmoore.com), or consult your local Yellow pages.

**Technical Data**

**Tintable White**

Vehicle Type	Acrylic Blended Latex
Pigment Type	Titanium Dioxide
Volume Solids	23%
Theoretical Coverage At	400 – 450 Sq. Ft.
Recommended Film Thickness	<i>Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.</i>
Recommended Film Thickness – Wet	4.0 Mills
– Dry	0.9 Mills
Dry Time @ 77° F	– Set To Touch 1/2 Hour
(25° C) @ 50% RH	– Dry To Touch 1 Hour
	– To Recoat 2–3 Hours
	– To Hard Dry 2–3 Hours
Dries By	Evaporation, Coalescence
Viscosity	94 ± 3 KU
Flash Point (Seta)	None
60° Specular Gloss	Flat
Surface Temperature at application – Min.	50° F
– Max.	90° F
Thin With:	Clean Water
Clean Up Thinner	Clean Water
Weight Per Gallon	10.39 lbs.
Storage Temperature – Min.	40 F
– Max.	90 F

**Volatile Organic Compounds (VOC)**  
*Unthinned, this product is formulated not to exceed 100 Grams/Liter\*\**

16. **Polyamide Epoxy Gloss Coating, Benjamin Moore M36/M37 or Equal.** High gloss extremely durable stain resistant film. Protect metal, masonry, plaster or drywall on interior or exterior surfaces. Resistant to impact, abrasion, acid, chemical alkali and strong cleaning compounds. Forms a waterproof barrier coat.

**Mixing Instructions:**

This two-component product is mixed as a 1 to 1 ratio by volume of components "A" to "B." First, mix each component separately until uniform, then combine components "A" & "B" and mix thoroughly (5 minutes) or until homogeneous. For best results, use a spiral mixing blade in a variable speed (400-600 rpm) electric drill. Place the spiral mixing blade at the bottom of the container before turning on the mixer. This will help avoid inducting air into the material. Inducted air will cause "bubbles" in the coating when applied. Gently move the mixer head up to the surface while running. Do not remove the head while it is still spinning. Allow the combined components to sit for an induction time of 30 minutes, then lightly stir again to ensure uniformity.

This product has a workable pot life of 6-8 hours at 70° F. Applying the material immediately after the 30 minute's induction time will provide best results.

**Note:** Higher air and mixture temperatures will decrease the pot life and working time.

- Colors: MUST BE MIXED WITH M37-84 CATALYST**
- Standard:†** Contact your Benjamin Moore & Co. Representative
  - Tint Bases:** M36-90 Tintable White  
M36-91 Deep Base  
M36-92 Clear Base
  - Special Colors:** Contact your Benjamin Moore & Co. Representative

**Certification:**

Master Painters Institute MPI #77.  
Formulated without lead, mercury, or chromates.  
Does not contain any ozone-depleting substances, either Class I or Class II.

† for Clear Sealer Finish reference Product Data Sheet M73 M37B0

**Analysis:**

typical —  
may vary by color

M36-90-H as mixed with M37-84

Pigment: 26.5%	
Titanium Dioxide . . . . .	88.6%
Inert Pigments . . . . .	11.2%
	100.0%

Vehicle: 73.5%	
Polyamide Epoxy Resin . . . . .	57.3%
Solvents & Additives . . . . .	16.2%
	100.0%

**Technical Data**

**Tintable White**

Generic Type	Polyamide Epoxy
Pigment Type	Titanium Dioxide and Select Inerts
Volume Solids (mixed as recommended)	55%
Theoretical Coverage	440 Sq. Ft. @ 2.0 Mils
Film Thickness – Wet	2.7 – 4.5 Mils
– Dry	1.5 – 2.5 Mils
Dry Time @ 70° F – To Touch	1 1/2 Hours
– To Recoat	8 Hours
Dries By	Chemical Cure
Dry Heat Resistance – Intermittent	400° F
Viscosity @ 70° F (mixed as recommended)	70 ± 5 KU
Flash Point (Seta)	81° F
60° Specular Gloss – Gloss	80–90%
Surface Temperature At Application – Min.	55° F
– Max.	90° F
Surface must be dry and at least 5' above the dew point	
Reducer	M95
Reduction* – Brush	Do not thin
– Roller	Do not thin
– Spray	Do not thin
Clean Up Thinner	M95
Mixing Ratio (by volume)	1:1
Induction Time	30 Minutes
Pot Life @ 70° F	6 – 8 Hours
Weight Per Gallon 0.497* as recommended)	10.2 lb
Storage Temperature – Min.	40° F
– Max.	90° F

**Volatile Organic Compounds (VOC)**

**Unthinned	Grams/Liter	420
	Lbs./Gal.	3.51

17. **D.T.M. Alkyd Low Lustre Enamel, Benjamin Moore Z163 or Equal.** Dual purpose primer and finish coat, rust preventive coating with interior and exterior application.

**Product Information**

**Colors: —Standard:**

Z163-01 White  
Z163-60 Bronzestone  
Z163-80 Black

**—Tint Bases:**

Z163-2B Medium  
Z163-3B Deep

**—Special Colors:**

Contact your BENJAMIN MOORE® representative.

**Certification:**

Formulated without lead, mercury, or chromates.  
Formulated with non-photochemically reactive solvents.

**Technical Assistance**

Available through your local authorized independent BENJAMIN MOORE® retailer.  
For the location of the retailer nearest you, call 1-800-826-2623, see [www.benjaminmoore.com](http://www.benjaminmoore.com), or consult your local Yellow Pages.

**Technical Data**

**Safety White**

Vehicle Type	Modified Alkyd
Pigment Type <sup>o</sup>	Corrosion Inhibitors & Titanium Dioxide
Volume Solids <sup>o</sup>	49%
Theoretical Coverage At Recommended Film Thickness	500-600 Sq. Ft.
<i>Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.</i>	
Recommended Film Thickness – Wet	3.1 – 5.1 Mills
– Dry	1.5 – 2.5 Mills
Dry Time @ 77° F — Set To Touch	1.5 Hours
(25° C) @ 50% RH — To Recoat	8 Hours
Dries By	Oxidation
Viscosity <sup>o</sup>	88 ± 5 KU
Flash Point (Seta)	103° F
60° Specular Gloss	40 – 60%
Surface Temperature at application – Min.	50° F
– Max.	90° F
Thin With:	Do Not Thin
Clean Up Thinner	Mineral Spirits
Weight Per Gallon <sup>o</sup>	10.7 lbs.
Storage Temperature – Min.	40° F
– Max.	90° F
Volatile Organic Compounds (VOC)	
<i>Unthinned, 397 Grams/Liter, 3.31 Lbs./Gallon</i>	

18. Urethane alkyd Gloss Enamel, Benjamin Moore P22 or Equal. Good color and gloss retention. Good abrasion resistance. Interior or exterior application. Two hours dry to touch.

Product Information																																															
<p><b>Labor Saving Benefits</b></p> <ul style="list-style-type: none"> <li>• Good color and gloss retention which lengthens the coating life</li> <li>• Good abrasion resistance permits wider application and longer coating life</li> <li>• Ready mixed line of colors eliminates the need to custom tint all colors</li> <li>• Available in unlimited custom colors satisfying the most stringent color needs</li> <li>• Versatile application by brush, roller and various spray methods</li> </ul>	<p><b>Technical Data<sup>o</sup></b></p> <table border="1"> <thead> <tr> <th></th> <th>Pastel Base</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td>Urethane Alkyd</td> </tr> <tr> <td>Pigment Type</td> <td>Titanium Dioxide</td> </tr> <tr> <td>Volume Solids</td> <td>49%</td> </tr> <tr> <td>Theoretical Coverage At Recommended Film Thickness</td> <td>375-425 Sq. Ft.</td> </tr> <tr> <td colspan="2"><i>Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.</i></td> </tr> <tr> <td>Recommended Film Thickness - Wet</td> <td>3.8 - 4.3 Mils</td> </tr> <tr> <td>- Dry</td> <td>1.8 - 2.1 Mils</td> </tr> <tr> <td>Dry Time @ 77° F</td> <td>— Set To Touch 2 Hours</td> </tr> <tr> <td>(25° C) @ 50% RH</td> <td>— To Recoat 8 Hours</td> </tr> <tr> <td>Dries By</td> <td>Oxidation</td> </tr> <tr> <td>Viscosity<sup>o</sup></td> <td>75 ± 5 KU</td> </tr> <tr> <td>Flash Point (Seta)</td> <td>103° F</td> </tr> <tr> <td>60° Specular Gloss</td> <td>85%</td> </tr> <tr> <td>Surface Temperature at application - Min.</td> <td>50° F</td> </tr> <tr> <td>- Max.</td> <td>95° F</td> </tr> <tr> <td>Thin With:</td> <td>Do Not Thin</td> </tr> <tr> <td>Clean Up Thinner</td> <td>Mineral Spirits</td> </tr> <tr> <td>Weight Per Gallon<sup>o</sup></td> <td>8.9 lbs.</td> </tr> <tr> <td>Storage Temperature - Min.</td> <td>40° F</td> </tr> <tr> <td>- Max.</td> <td>90° F</td> </tr> <tr> <td colspan="2"><b>Volatile Organic Compounds (VOC)<sup>o</sup></b></td> </tr> <tr> <td colspan="2">394 Grams / Liter 3.29 LBS / Gallon</td> </tr> </tbody> </table>		Pastel Base	Vehicle Type	Urethane Alkyd	Pigment Type	Titanium Dioxide	Volume Solids	49%	Theoretical Coverage At Recommended Film Thickness	375-425 Sq. Ft.	<i>Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.</i>		Recommended Film Thickness - Wet	3.8 - 4.3 Mils	- Dry	1.8 - 2.1 Mils	Dry Time @ 77° F	— Set To Touch 2 Hours	(25° C) @ 50% RH	— To Recoat 8 Hours	Dries By	Oxidation	Viscosity <sup>o</sup>	75 ± 5 KU	Flash Point (Seta)	103° F	60° Specular Gloss	85%	Surface Temperature at application - Min.	50° F	- Max.	95° F	Thin With:	Do Not Thin	Clean Up Thinner	Mineral Spirits	Weight Per Gallon <sup>o</sup>	8.9 lbs.	Storage Temperature - Min.	40° F	- Max.	90° F	<b>Volatile Organic Compounds (VOC)<sup>o</sup></b>		394 Grams / Liter 3.29 LBS / Gallon	
	Pastel Base																																														
Vehicle Type	Urethane Alkyd																																														
Pigment Type	Titanium Dioxide																																														
Volume Solids	49%																																														
Theoretical Coverage At Recommended Film Thickness	375-425 Sq. Ft.																																														
<i>Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.</i>																																															
Recommended Film Thickness - Wet	3.8 - 4.3 Mils																																														
- Dry	1.8 - 2.1 Mils																																														
Dry Time @ 77° F	— Set To Touch 2 Hours																																														
(25° C) @ 50% RH	— To Recoat 8 Hours																																														
Dries By	Oxidation																																														
Viscosity <sup>o</sup>	75 ± 5 KU																																														
Flash Point (Seta)	103° F																																														
60° Specular Gloss	85%																																														
Surface Temperature at application - Min.	50° F																																														
- Max.	95° F																																														
Thin With:	Do Not Thin																																														
Clean Up Thinner	Mineral Spirits																																														
Weight Per Gallon <sup>o</sup>	8.9 lbs.																																														
Storage Temperature - Min.	40° F																																														
- Max.	90° F																																														
<b>Volatile Organic Compounds (VOC)<sup>o</sup></b>																																															
394 Grams / Liter 3.29 LBS / Gallon																																															
<p><b>Colors: —Standard:</b></p> <table border="0"> <tr> <td>P22-08 Safety White</td> <td>P22-64 Bronzestone</td> </tr> <tr> <td>P22-15 Safety Yellow</td> <td>P22-65 Safety Orange</td> </tr> <tr> <td>P22-21 Safety Red</td> <td>P22-73 Platinum Gray</td> </tr> <tr> <td>P22-35 Safety Blue</td> <td>P22-75 Battleship Gray</td> </tr> <tr> <td>P22-60 Brown</td> <td>P22-82 Safety Black</td> </tr> </table>	P22-08 Safety White	P22-64 Bronzestone	P22-15 Safety Yellow	P22-65 Safety Orange	P22-21 Safety Red	P22-73 Platinum Gray	P22-35 Safety Blue	P22-75 Battleship Gray	P22-60 Brown	P22-82 Safety Black																																					
P22-08 Safety White	P22-64 Bronzestone																																														
P22-15 Safety Yellow	P22-65 Safety Orange																																														
P22-21 Safety Red	P22-73 Platinum Gray																																														
P22-35 Safety Blue	P22-75 Battleship Gray																																														
P22-60 Brown	P22-82 Safety Black																																														
<p><b>BENJAMIN MOORE<sup>o</sup> COLOR PREVIEW<sup>o</sup> Tint BASES—</b></p> <table border="0"> <tr> <td>P22-1B Pastel</td> <td>P22-2B Medium</td> </tr> <tr> <td>P22-3B Deep</td> <td>P22-4B Ultra</td> </tr> </table>	P22-1B Pastel	P22-2B Medium	P22-3B Deep	P22-4B Ultra																																											
P22-1B Pastel	P22-2B Medium																																														
P22-3B Deep	P22-4B Ultra																																														
<p><b>—Special Colors:</b></p> <p>Contact your Benjamin Moore &amp; Co. representative.</p>																																															
<p><b>Certification:</b></p> <p>VOC compliant in National AIM, OTC and CARB regulated areas</p> <p>Master Painters Institute MPI # 9 &amp; 48</p>																																															
<p><b>Technical Assistance</b></p> <p>Available through your local authorized independent Benjamin Moore<sup>o</sup> retailer.</p> <p>For the location of the retailer nearest you, call 1-800-826-2623, see <a href="http://www.benjaminmoore.com">www.benjaminmoore.com</a>, or consult your local Yellow Pages.</p>																																															

19. **Latex Floor & Patio Enamel Benjamin Moore 122 or Equal.** Premium quality, quick drying, epoxy-modified acrylic satin latex floor enamel. Resistant to soaps and detergents, grease and oil.

**Product Information**

**Colors: —Standard:**  
White and a variety of ready-mixed colors

**—Tint Bases:**  
BENJAMIN MOORE® COLOR PREVIEW® bases 1B, 2B, & 3B

**—Special Colors:**  
Contact your Benjamin Moore & Co. representative

**Certification:**  
Formulated without lead, mercury, or chromates.  
Very low in VOCs.

**Technical Assistance**  
Available through your local authorized independent BENJAMIN MOORE® retailer. For the location of the retailer nearest you, call 1-800-826-2623, see [www.benjaminmoore.com](http://www.benjaminmoore.com), or consult your local Yellow Pages.

**Technical Data** **White**

Vehicle Type	Epoxy-Modified Acrylic Latex
Pigment Type <sup>9</sup>	Titanium Dioxide
Volume Solids <sup>9</sup>	30%
Theoretical Coverage At Recommended Film Thickness	350 – 550 Sq. Ft.
<i>Depending on surface texture and porosity Be sure to estimate the right amount of product for the job. This will ensure color uniformity and minimize the disposal of excess paint.</i>	
Recommended Film Thickness – Wet	2.9 mils
– Dry	0.9 mils
Dry Time @ 77° F — Set To Touch	1 Hour
(25° C) @ 50% RH — Dry To Touch	4 Hours
– To Recoat	Overnight
– To Service	24 Hours
Dries By	Evaporation, Coalescence
Viscosity <sup>9</sup>	78 ± 2 KU
Flash Point (Seta)	None
60° Specular Gloss	Pearl
Surface Temperature at application – Min.	50 F
– Max.	90 F
Thin With	Clean Water
Clean Up Thinner	Clean Water
Weight Per Gallon <sup>3</sup>	10.3 lbs.
Storage Temperature – Min.	40° F
– Max.	90° F

**Volatile Organic Compounds (VOC)**  
*Unthinned, this product is formulated  
not to exceed 250 Grams Liter. \*\**

20. **Penetrating Interior Wood Stain, Benjamin Moore 234 or Equal.** Rapid drying, uniform penetration. For use on wood furniture, paneling, doors, trim, floors, and cabinets

**Product Information**

**Colors: —Standard:**

A range of popular wood colors plus Pickling White (71)  
(Do not add tinting colorants to adjust stains. Except Pickling White: up to 4.0 fl. oz. Benjamin Moore & Co. Color Preview<sup>®</sup> colorants per gallon.)

**—Tint Bases:**

Not available

**—Special Colors:**

Contact your Benjamin Moore & Co. representative

**Certification:**

Formulated with non-photochemically reactive solvents.  
Formulated without lead or mercury.

**Federal Specifications Generic Equivalent**

TT-S-720-A

**Technical Assistance**

Available through your local authorized independent Benjamin Moore & Co. dealer. For the location of the dealer nearest you, call 1-800-826-2623, see [www.benjaminmoore.com](http://www.benjaminmoore.com), or consult your local Yellow Pages.

**Technical Data**

**Cherry**

Vehicle Type	Alkyd/Oil
Pigment Type <sup>o</sup>	None/TiO <sub>2</sub>
Volume Solids <sup>o</sup>	31%
Theoretical Coverage At Recommended Film Thickness	500 – 600 Sq. Ft.
Recommended Film Thickness – Wet – Dry	Minimal Minimal
Dry Time @ 77° F — To Recoat (25° C) @ 50% RH — To Service	3 to 4 Hours Overnight
Dries By	Evaporation, Oxidation
Viscosity <sup>o</sup>	<50 KU
Flash Point (Seta)	Combustible
60° Specular Gloss	Flat
Surface Temperature at application – Min. – Max.	50° F 90° F
Thin With	Do Not Thin
Clean Up Thinner	Mineral Spirits
Weight Per Gallon <sup>o</sup>	7.2 lbs.
Storage Temperature – Min. – Max.	40° F 90° F

Volatiles Organic Compounds (VOC)  
Unthinned, this product is formulated  
not to exceed 550 Grams/Liter\*\*

21. Rubber Based Swimming Pool Paint, Insl-x Products RP2700 series or Equal.

<b>PRODUCT NAME:</b>	Rubber Based Swimming Pool Paint
<b>PRODUCT NUMBERS:</b>	RP-2700 Series
<b>DESCRIPTION:</b>	Insl-X RP Series pool paint is a rubber base coating for all new or old concrete pools. This product complies with all volatile emission standards outlined by the Ozone Transport Commission. Insl-X RP Series pool paint provides a durable satin finish for use in residential and commercial pools. Suitable for use in fresh or salt water Resists fading, fungus, algae, abrasion and alkalis.
<b>SUGGESTED USES:</b>	Concrete, Gunnite*, Marcite*, Pools <i>*Integrity of marcite or gunnite must be sound and solid.</i>
<b>COLORS:</b>	Ocean Blue                      Aquamarine                      Royal Blue White                              Black
<b>FINISH:</b>	Satin finish
<b>VEHICLE TYPE:</b>	Synthetic Rubber
<b>SOLVENT TYPE:</b>	Aromatic and Aliphatic Hydrocarbons
<b>VOC:</b>	Less than - 2.8 Lbs/ gal VOC ( 340 gms. /liter )
<b>WET HEAT RESISTANCE:</b>	95°F maximum
<b>FLASH POINT:</b>	54°F Seta Flash
<b>SOLIDS BY VOLUME:</b>	58 % +/- 1%
<b>WEIGHT PER GALLON:</b>	12.75 lbs. +/- .15 lbs.
<b>RECOMMENDED DRY FILM:</b>	2 mils per coat. Apply a minimum of 2 coats on new surfaces
<b>COVERAGE:</b>	Theoretical coverage is 461 square feet per gallon at two mils dry. Material losses during mixing and application will vary and must be taken into consideration when estimating job requirements.
<b>VISCOSITY:</b>	70-80 KU
<b>RECOMMENDED DRY TIME:</b>	Set to touch in 30 minutes, Re-coat in 24 hours
<b>REDUCER:</b>	TH-0208. Do not thin if doing so would result in exceeding VOC limitations.
<b>CLEAN UP:</b>	TH-0208
<b>PHYSICAL PROPERTIES:</b>	Resists Mildew, Algae, Fresh & Salt Water, Suntan Oils.
<b>RECOMMENDED PRIMERS:</b>	Self Priming

ALL FREIGHT CHARGES ARE TO BE INCLUDED. ANY BIDDER CHARGING FREIGHT WILL BE DISQUALIFIED.

NO MINIMUM REQUIREMENTS FOR DELIVERY. ANY BIDDER SETTING MINIMUMS MAY BE DISQUALIFIED.

**AWARDING:** The Town may award this bid in whole or in parts, or make no award at all, whichever is in the best interest of the Town.